

Model		DRP-480-24	DRP-480-36	DRP-480-48
Output	DC output Voltage	24V	36V	48V
	Voltage tolerance	±1.0%	±1.0%	±1.0%
	Rated Current	20A	13.5A	10A
	Related Power	480w	480w	480w
	Wave&Noise	80mVp-p	150mVp-p	150mVp-p
	Adjustable range for DC Voltage	±10%	±10%	±10%
	Set up,rise,hold up time	800ms 40ms 20ms		
Input	Voltage Range			
	Input Current	4.5A/115VAC 0.5A/230VAC		
	Efficiency	80%	85%%	85%
	AC inrush current	Cold start current 15A/115V 30A /230VAC		
	Leakage current	<0.5mA/240VAC		
Protection	Overload	Protection type: cutoff output, recovery after restart power		
	Over voltage	13.8V-16.2V		55.2V-64.8V
		Hiccup mode,recovers automatically after fault condition		
Environment	Working temp humidity			
	Stor temp, humidity	-20~+85°C 20%~90%RH Non-condensing		
Safety	Withstand voltage	I/P-FG:1.5KVAC 1min		
		O/P-FG:0.5KVAC 1min		
Standard	Safety standard			
	Refer	Design refer to GB4943,UL60950,EN60950		
	EMC standard	Design refer to GB9254,EN55022 Class A		
Size	227*125.2*100mm			
	Package	1.2kg, 16 pcs/20kg		